
C175-16 Generator Set

Electric Power



Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

Specifications

Generator Set Specifications	
Minimum Rating	2500 kVA
Maximum Rating	3100 kVA
Emissions/Fuel Strategy	Low Fuel, Low Emissions
Voltage	380 to 11000 Volts
Frequency	50 Hz
Speed	1500 rpm
Duty Cycle	Standby, Mission Critical, Prime, Continuous

Engine Specifications		
Engine Model	C175-16 SCAC, V-16, 4-Stroke Water-Cooled Diesel	
Bore	175 mm	6.89 in
Stroke	220 mm	8.66 in
Displacement	84.7 l	5166.88 in³
Compression Ratio	16:07:01	
Aspiration	Turbo Aftercooled	
Fuel System	Common Rail	
Governor Type	ADEM™ A4	

Generator Set Dimensions		
Length - Minimum	6137 mm	241.6 in
Length - Maximum	7900 mm	311 in
Width - Minimum	2110 mm	83 in
Width - Maximum	2786 mm	108.5 in
Height - Minimum	2211 mm	87 in
Height - Maximum	3307 mm	130.2 in

© 2019 Caterpillar All Rights Reserved

Dry Weight - Genset (minimum)	19391 kg	42750 lb
Dry Weight - Genset (maximum)	23020 kg	50750 lb

Benefits and Features

Cat Generator Set Package

- Cat generator set packages have been fully prototype tested
- Accepts 100% block load in one step and meets NFPA 110 loading requirements
- Conform to ISO 8528-5 steady state and transient response requirements

Cat Diesel Engine

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

SR5 Alternator

- Superior motor starting capability minimizes need for oversizing alternator
- Designed to match performance and output characteristics of Cat diesel engines
- Robust Class H insulation

EMCP 4 Control Panel

- User-friendly interface and navigation
- Scalable system to meet a wide range of installation requirement
- Expansion modules and site-specific programming for specific customer requirements

Cooling System

- Designed to operate in standard ambient temperatures up to 50°C (122°F)
- Contact your Cat Dealer for specific ambient and altitude capabilities

Certifications

- IBC Seismic Certification
- EU Certification of Conformance (CE)
- EEC Declaration of Conformity

One Safe Source

- Components used in the generator set are selected at the design stage to provide optimum package performance
- The generator set is fully assembled at a Caterpillar facility following our quality guidelines
- Each generator set package is tested before leaving the Caterpillar facility
- Cat product support, including dealer service, parts and warranty covers the entire Cat power system

World Wide Product Support

- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- Your local Cat dealer provides extensive post-sale support, including maintenance and repair agreements

Standard Equipment

Air Inlet System

- 4 x Single element canister with service indicator(s)

Control Panel

© 2019 Caterpillar All Rights Reserved

- EMCP4 / EMCP4.2
- Engine cool-down timer.
- Frequency (Hz)
- RPM
- Lamp test
- True RMS AC metering, 3-phase, +/-2% accuracy
- Failure to start (overcrank)
- Controls
- Alarm acknowledge
- Speed adjust
- Digital Indicators
- 4 Programmable relay outputs (Form A)
- Coolant temperature
- Oil pressure (psi, kPa or bar)
- Programmable Protective Relaying Functions
- Reverse power
- Volts (L-L & L-N)
- Overspeed
- Emergency stop pushbutton
- Overcurrent
- 2 Programmable relay outputs (Form C)
- Reverse Reactive Power
- Low coolant level
- Serial annunciator module data link
- Communications
- 6 Programmable digital inputs
- Text alarm / event descriptions.
- Warning / shutdown Indicators
- Amps (per phase & average)
- Accessory module data link
- Customer data link (Modbus RTU)
- Low coolant temperature
- 24 Volt DC operation
- Over / under voltage
- High coolant temperature
- Engine cycle crank
- Generator mounted - rear facing
- Emergency stop

© 2019 Caterpillar All Rights Reserved

- 2 Programmable digital outputs
- Power Factor (per phase & average)
- Auto / start / stop control.
- Generator phase sequence
- Operating hours
- Over / under frequency
- Environmental sealed front face.
- DC Volts
- Low oil pressure

Cooling System

- SCAC cooling
- Coolant Sensors
- Coolant drain line and valves
- Radiator group - shipped loose
- Fan and belt guards

Exhaust System

- Bolted flange, with bellow for each turbo
- Dry Exhaust Manifold

Fuel System

- Filters x 3
- Secondary / Tertiary fuel filters
- 4 Micron Spin On Type
- 10 Micron Spin On Type
- Primary fuel filter water / fuel water separator
- Engine mounted filters X3

Generator and Attachments

- 6 Leads
- IEC Platinum stator RTDs
- Voltage Regulator
- Voltage regulator
- Reactive droop capability
- 3 Phase voltage sensing
- RFI suppression
- Min / max exciter limiter
- exciter diode monitor
- Form Wound
- Permanent magnet
- NEMA Class H insulation

© 2019 Caterpillar All Rights Reserved

- Class H temperature rise at 40C ambient
- (LV) Busbar connections, top/center mounted, top cable entry
- Salient pole
- 3 Phase Brushless
- 50 Hz models: IEC standard hole pattern
- (MV) Busbar connections, right side extension box, bottom cable entry
- Anti condensation space heater
- Class F temperature rise at 40C ambient
- Right side extension box, bottom cable entry

Governing System

- ADEM A4
- Redundant shutdown (Overspeed protection through a duplicate speed sensing system)

Lube System

- Oil filter, filler and dipstick
- Integral lube oil cooler
- Oil drain lines and valve
- Gear type lube oil pump
- Fumes disposal
- Lubricating oil
- Prelube - required with prime, continuous, and standby

Mounting Systems

- Battery disconnect switch
- Rubber anti-vibration mounts (shipped loose)
- Batteries and battery rack w/cables
- Dual 24 volt electric starting motors
- Rails - Engine / generator

Service Instructions

- Two PM inspections

Power Termination

- Bus Bar

General

- Paint - Caterpillar yellow with high gloss black rails & radiator
- Right hand service
- Flywheel and flywheel housing-SAE No. 00
- SAE standard rotation

Optional Equipment

Air Inlet System

© 2019 Caterpillar All Rights Reserved

- Single element air cleaner
- Dual element air cleaner
- Air inlet adapters
- Air inlet protection

Control Panel

- EMCP 4.3, EMCP 4.4
- EMCP 4.4 optional harness
- EMCP and MV&HV power connection locations
- Load share module
- EMCP mounting location - LV / MV
- Customer AC-DC connection mounting location - LV/MV
- Load share module / auxiliary plate and auxiliary box (LV)
- Load share governor
- Frame boxes
- Automatically selected ground
- EMCP voltage and current sensing groups
- Raise lower switch
- Speed adjust
- Annunciator modules
- Customer interface options
- Generator temperature monitoring
- Modbus monitoring of packages
- E-Stop
- Interconnect harness
- Generator Harness

Cooling System

- Package mounted radiator
- Remote radiators
- Fuel cooler

Exhaust System

- Front housing - Standby or mission critical
- Front housing - Prime or continuous
- Exhaust collectors / Manifold
- Exhaust support group
- Mufflers
- Weld flanges
- Aftercooler drain

Crankcase Systems

© 2019 Caterpillar All Rights Reserved

- Explosive relief valves
- Crankcase ventilation system

Fuel System

- Primary fuel filter

Generators and Attachments

- Low voltage - 1800 and 3000 Frames - 50 Hz, 3 phase, 1500 rpm, FW, PM, No of leads=6, Pitch 0.6667
- Medium Voltage - 1800 and 3000 Frames - 50 Hz, 3 phase, 1500 rpm, FW, PM, No of leads=6, Pitch 0.6667
- Low Voltage - 1800 and 3000 Frames - 60 Hz, 3 phase, 1800 rpm, FW, PM, No of leads=6, Pitch 0.6667
- Space heater kit
- Thermostat for space heater
- Conversion GP-Top cable entry
- Generator air intake
- Differential current transformers

Instrumentation

- Pyrometer and thermocouples

Lube System

- Lube oil heater
- Drain group oil pans
- Lubricating oil
- Electric prelube pumps
- Oil filters

Mounting

- Rubber anti-vibration mounts
- Spring type linear vibration isolators
- IBC vibration isolators - Shipped loose

Power Connections

- Center post busbars (LV)
- Side / Rear mounted busbars (LV)
- Harnesses (Breaker)
- Cable entry options (LV)
- Enclosures - Control packaging (LV)
- Power connection covers (LV)
- Neutral ground (LV)
- 1800 Frame generators circuit breaker
- Masterpack breakers
- Paralleling circuit breakers
- 1800 Frame generator side / rear mounted busbars (MV)
- Cable entry options (MV)

© 2019 Caterpillar All Rights Reserved

- Neutral ground (MV)
- Low voltage connection cable
- Masterpack breaker connections

Special Tests / Reports

- Generator test report
- PGS test report @ 1.0 power factor
- PGS test report @ 0.8 power factor
- Standard genset TVA (Torsional Vibration Analysis) report
- Custom genset TVA report
- Special test charge - Engine only
- Genset fuel consumption test
- Standard engine test charge
- IBC seismic certification
- OSCOSH1 seismic certification

Starting / Charging System


- 24 Volt power distribution box
- 24 Volt electric starting motors
- Air starting motor
- Air pressure regulator
- Starter location covers
- 24 Volt battery sets - Dry
- Heavy duty battery sets with rack
- 20 Amp battery chargers
- 35 Amp battery chargers
- 50 Amp battery chargers
- Charging alternators - Dry
- Jacket water heaters
- Jacket water heater wiring groups

General

- Special paint colors
- Service tools - Engine barring group
- Barring group manual
- Engine barring air powered
- Control GP - Air powered bar group

© 2019 Caterpillar All Rights Reserved

Dimensional Art



Dimensions	Dimension 1	Dimension 2	Dimension 3
Genset dimensions	7900 mm (311.0 in)	2756 mm (108.5 in)	3307 mm (130.2 in)

The International System of Units (SI) is used in this publication.
CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

© 2019 Caterpillar All Rights Reserved

Rating Type: PRIME

Fuel Strategy: LOW FUEL CONSUMPTION




Image shown may not reflect actual configuration

C175-16
2180 ekW/ 2725 kVA
50 Hz/ 1500 rpm/ 400 V

	Metric	English
Package Performance		
Genset Power Rating with Fan @ 0.8 Power Factor	2180 ekW	
Genset Power Rating	2725 kVA	
Aftercooler (Separate Circuit)	48.0 ° C	118.4 ° F
Fuel Consumption		
100% Load with Fan	559.6 L/hr	147.8 gal/hr
75% Load with Fan	429.5 L/hr	113.5 gal/hr
50% Load with Fan	307.5 L/hr	81.2 gal/hr
25% Load with Fan	187.1 L/hr	49.4 gal/hr
Cooling System[1]		
Engine Coolant Capacity	N/A	N/A
Radiator Water Capacity High Temp Circuit	583 L	154 gal
Radiator Water Capacity Low Temp Circuit	121 L	32 gal
Radiator Total Capacity	704 L	186 gal
Inlet Air		
Combustion Air Inlet Flow Rate	175.7 m³/min	6205.3 cfm
Max. Allowable Combustion Air Inlet Temp	50 ° C	121 ° F
Exhaust System		
Exhaust Stack Gas Temperature	476.2 ° C	889.2 ° F
Exhaust Gas Flow Rate	456.9 m³/min	16132.1 cfm
Exhaust System Backpressure (Maximum Allowable)	N/A	N/A

© 2019 Caterpillar All Rights Reserved

Rating Type: PRIME

Fuel Strategy: LOW FUEL CONSUMPTION

Heat Rejection		
Heat Rejection to Jacket Water	1047 kW	59569 Btu/min
Heat Rejection to Exhaust (Total)	2063 kW	117309 Btu/min
Heat Rejection to Aftercooler	N/A	N/A
Heat Rejection to Atmosphere from Engine	165 kW	9356 Btu/min
Heat Rejection to Atmosphere from Generator	86 kW	4896 Btu/min

Alternator[2]	
Motor Starting Capability @ 30% Voltage Dip	7645 skVA
Current	3933 amps
Frame Size	1868
Excitation	PM
Temperature Rise	105 ° C

Emissions (Nominal)[3]		
NOx	4524.1 mg/Nm³	8.2 g/hp-hr
CO	133.5 mg/Nm³	0.3 g/hp-hr
HC	81.8 mg/Nm³	0.2 g/hp-hr
PM	18.5 mg/Nm³	0.0 g/hp-hr

DEFINITIONS AND CONDITIONS

1. For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

2. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40° C ambient per NEMA MG1-32.

3. Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

© 2019 Caterpillar All Rights Reserved

Rating Type: PRIME

Fuel Strategy: LOW FUEL CONSUMPTION

Applicable Codes and Standards:
AS1359, CSA C22.2 No100-04, UL142,UL489, UL869, UL2200,
NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC60034-1, ISO3046, ISO8528,
NEMA MG1-22,NEMA MG1-33, 2006/95/EC, 2006/42/EC, 2004/108/EC.

Note: Codes may not be available in all model configurations. Please consult your local Cat Dealer representative for availability.

PRIME: Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated ekW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

Fuel Rates are based on fuel oil of 35º API [16º C (60º F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29º C (85º F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

Performance No.: DM8720-06

Feature Code: 175DRA1

Generator Arrangement: 3723068

Date: 07/30/2019

Source Country: U.S.

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

© 2019 Caterpillar All Rights Reserved