




VESSEL WT. EMPTY: 1852 LBS.

BILL OF MATERIAL

MARK NO.	QTY	PART NUMBER	DESCRIPTION	MATERIAL
1	2	HS024000875CA	HEAD 24" OD 2:1 ELLIP 7/8" NOM 0.8125" MIN	SA-516-70N
2	1	HANO-467524016	SHELL 24" X 7/8" X 5'-0" ROLLED	SA-516-70
3	1	PP24008ECJ	PIPE ERW 24" S/10 X 1'-2 3/8" LG (BOE-PBE)	SA-53-B
4	1	PP0200JSCA	PIPE SMLS 2" S/80 X 3 1/8" LG (BOE-POE)	SA-106-B
5	2		PIPE SMLS 2" S/80 X 9" LG (BOE-POE)	SA-106-B
6	1	FWTS0200JCA	TEE BW 2" X 2" X 2" SCH 80	SA-234-WPB
7	1	FOCLO050LCA	COUPL-O-LET 1/2" 6000#	SA-105
8	3	FOCLO075LCA	COUPL-O-LET 3/4" 6000#	SA-105
9	3	FOCLO100LCA	COUPL-O-LET 1" 6000#	SA-105
10	2	FFCFO200TYSJCA	COUPLING 2" 3000# THRD X SW	SA-105
11	2	FOTLO200JCA	THREAD-O-LET 2" 3000#	SA-105
12	1	NANE-HANOVESSEL08	NAMEPLATE 5" X .06" X 6" LG CODE	316 SS
14	1	STANO300X0300X0037CE	ANGLE 3" X 3" X 3/8" X 3" LG	SA-36
15	2	STCS1000X0153CE	CHANNEL 10" @ 15.3#/FT X 3" LG	SA-36
16	2	HANO-464483011	LIFT LUG 1/2" X 6 1/2" X 7 1/4" W/3" HOLE 10,000#	SA-516-70
17	1	PLVG0500CA	PLATE 1/2" X 2'-7" OD	SA-516-70



DETAIL PS-1 & PS-2
SCALE 3/4"=1'-0" (2 REQ'D)

REPAIR NOTES

1. DRILL AND TAP 1/4" NPT TELLTALE HOLES THRU EACH REINFORCING PAD. LOCATE THE CENTER OF THE HOLE 3/4" FROM THE OUTER EDGE. REPAIR SHOULD BE PLACED ON VESSEL SO THAT WELDLINE IS ORIENTED AT THE LOW POINT OF THE NOZZLE WHEN THE VESSEL IS IN SERVICE.
2. INSIDE EDGES OF NOZZLE NECKS SHALL BE ROUNDED TO 0.125" RAD OR HALF THE WALL THICKNESS IF LESS THAN 0.250".
3. ALL DIMENSIONS ARE ± 0.125" EXCEPT AS NOTED.
4. ALL HEAD TO SHELL WELD JOINTS TO REFERENCE W1 (SEE WELD FIGURES).
5. ALL INSIDE COMPONENTS ARE SEAL WELDED, 3/16" MIN.
6. IF CODE CASE 2235 IS UTILIZED THE STAMPING WILL BE UT. IF RT IS UTILIZED W/UT, THE APPROPRIATE RT STAMPING WILL BE APPLIED WITH THE UT STAMPING.
7. WELD PROCEDURES: g₁-1-1_N_u-h, g₁-11-12_N_u-v-20, mm-1-1_N_u-h, g₁-11-12_pu-cc-20, g₁-81-11_N_u-v-50

FABRICATION & WELD NOTES

DESIGN PRESSURE: 1440 P.S.I. DESIGN TEMPERATURE: 350 °F
RADIOGRAPH RT-2 STRESS RELIEVE: NO
CORROSION ALLOWANCE: 0" HYDROSTATIC TEST: 1872 P.S.I.
VESSEL JOINT EFFICIENCY: 100 %
INITIAL TEST: N/A P.S.I.
HAMMER TEST: N/A P.S.I.
STRENGTH OF 70,000 P.S.I.
HEAD THICKNESS DETERMINED USING A TENSILE
STRENGTH OF 70,000 P.S.I.
PAINT: SEE SPECIFICATIONS
CLEAN ALL SURFACES THOROUGHLY AND PAINT
AS FOLLOWS
PRIMER: FINISH:

GENERAL NOTES

2013 EDITION, --- ADDENDA
CONSTRUCTION SECT. VIII
ASME CODE DIV. I
APPLY SYMBOL PER PAR. UC-116

EXTERRAN
ISSUED FOR CONSTRUCTION

DATE:
SIGN:

CUSTOMER

EXTERRAN STOCK

TITLE

24" OD X 5'-0" S/S @ 1440#
VERTICAL BLOWCASE ~ V-115

DRAWN

DATE

APPROVED

SCALE

AS NOTED

NO. REQ'D

DRAWING NO.

HANO-485524020

SHEET NO.

1 of 1

REV.

1

NB	QTY	SIZE	ASA RATING	TYPE & FINISH	SERVICE	I. S. PROJ.	O. S. PROJ.	WELD FIG. NO.	I. S. FILET	O. S. FILET	PAD FILET
N6B	1	1/2"	6000#	COUPL-O-LET	PRESSURE INDICATOR	-	-	W13	-	1/4"	-
N8	1	3/4"	6000#	COUPL-O-LET	TEMPERATURE INDICATOR	-	-	W13	-	1/4"	-
N7B	1	3/4"	6000#	COUPL-O-LET	LEVEL GAUGE	-	-	W13	-	1/4"	-
N7A	1	3/4"	6000#	COUPL-O-LET	LEVEL GAUGE	-	-	W13	-	1/4"	-
N6B	1	1"	6000#	COUPL-O-LET	LEVEL SWITCH	-	-	W13	-	1/4"	-
N6A	1	1"	6000#	COUPL-O-LET	LEVEL SWITCH	-	-	W13	-	1/4"	-
N4	1	2"	3000#	COUPLING	DRAIN	-	BE BUD	W2	-	3/8"	-
N3	1	2"	3000#	COUPLING	LIQUID INLET/OUTLET	-	BE BUD	W2	-	3/8"	-
N2B	1	2"	3000#	THREAD-O-LET	LIQUID LEVEL CONTROL	-	-	W10	-	3/8"	-
N2A	1	2"	3000#	THREAD-O-LET	LIQUID LEVEL CONTROL	-	-	W10	-	3/8"	-
N1	1	1"	6000#	COUPL-O-LET	GAS OUTLET	-	-	W13	-	3/8"	-

SCHEDULE OF OPENINGS

REV.	DESCRIPTION	DATE	BY	CK
1	REVISED TO REMOVE N3 & ROTATE N5A, N6B & N6	4/25/11	JLV	

REVISIONS

TOLERANCES	THIS DRAWING IS THE PROPERTY OF EXTERRAN AND IS NOT TO BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED.
CUTS ±1/8"	
ANGLES ±1/2"	
WELD ASSY. ±1/4"	
WIP NO.	
ITEM NO.	

EXTERRAN
2207 FM 949
AILEYTON, TEXAS 75835
PH. 979-732-2327